

DYNAMICS OF THE LINEAR PNEUMATIC ACTUATOR

COMPUTER SIMULATION

SYMBOL	NAME	UNIT	VALUE
D	piston diameter	[m]	0.100
d	piston rod diameter	[m]	0.032
S	piston stroke	[m]	0.050
m	mass load	[kg]	parameter
F	force load	[N]	parameter
f	inlet area = outlet area	[m ²]	parameter
μ_1	inlet flow coefficient (1)	[-]	parameter
μ_2	outlet flow coefficient (2)	[-]	parameter
p_z	supply pressure	[Pa]	parameter
p_a	ambient pressure	[Pa]	100000
p_1	pressure in the inlet chamber (1)	[Pa]	result of simulation
p_2	pressure in the outlet chamber (2)	[Pa]	result of simulation
s	piston position	[m]	result of simulation
v	piston velocity	[m/s]	result of simulation
t	time line	[s]	result of simulation

MASS AIR-FLOW MODEL St. Venant-Wantzel

$$\dot{m} = \mu \cdot f \cdot p_A \cdot \sqrt{\frac{\kappa}{R \cdot T_0}} \cdot \sqrt{\frac{2}{\kappa - 1}} \cdot \Phi(\varepsilon) \quad \varepsilon = \frac{p_B}{p_A} \quad \Phi(\varepsilon) = \begin{cases} \sqrt{\frac{2}{\varepsilon^{\frac{\kappa}{\kappa-1}} - \varepsilon^{\frac{\kappa+1}{\kappa-1}}}} & \text{for } 0.52828 < \varepsilon \leq 1 \\ 0.25880 & \text{for } 0 < \varepsilon \leq 0.52828 \end{cases}$$

for the inlet chamber: $\mu = \mu_1 \quad p_A = p_z \quad p_B = p_1$

for the outlet chamber: $\mu = \mu_2 \quad p_A = p_2 \quad p_B = p_a$